





Doc	Description	Motorial Tyres	Si-o	
Pos.	Description	Material, Type	Size	
1	Cover, insulated	PE	D760	
2	Service opening, insulated	PE	D760	
3	Tank cylinder, double wall	PE100	ID700, SN2, L1470	
4	Cable inlet pipe	PE100	D50 SDR17	
5	Quick-coupling	PE	D50, 1 1/2"ext	
6	Ball valve	AISI316	D50, 1 1/2"int	
7	Reducer	PE100	D40-50	
8	Pressure pipe	PE100	D50 SDR17	
9	Outlet pipe	PE100	D50 SDR17	
10	Inlet pipe	PE100	D160 SDR33	
11	Pump - Wilo Drain TMW 32/8-10M	with floating switch	H _{max} =7m, Q _{max} =10m3/h	
12	Transition	PE100	D40 - 1 1/4"	
13	Bottom	PE100	20 mm	
14	Alarm device Tank-Check TC-412	Optional	□ YES / NO □	

Drawn: E.Ehala		Rain Water Pumping Station ID700 STRONG			
Approved:	J.Karolin		Plastic cover / Wilo Drain TMW 32/8-10M		
		www.iwsgroup.ee	Mass: kg	Product code:	Rev.
Innovative Water Systems			~80	500703 / standard drawing	3